

# 24 Ports Managed Industrial Ethernet Switch

24\*GE+4\*GF+1\*Console Industrial Ethernet Switch



- L2+ network management function, IPV4/IPV6 management support layer2 of software line speed forwarding;
- Switching capacity:56Gbps, MAC table:32K;
- Port can be real-time network management, timed on/off, can force LED working mode, real-time display of port power;
- Compatible with 1U rack, built-in internal power adapter;

**RoHS FCC CE**

## Introduction

The XC-IS3824GM series is a 1G uplink L2+ managed Industrial Ethernet switch. It has 24\*10/100/1000Base-T RJ45 ports and 4\*1G SFP fiber slot ports. Supports IPV4/IPV6 management, supports static route full line rate forwarding, supports complete security protection mechanism, complete ACL/QoS policy and rich VLAN functions, and is easy to manage and maintain. Supports multiple network redundancy protocols STP/RSTP/MSTP (<50ms) and (ITU-T G.8032) ERPS to improve link backup and network reliability. When one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications. According to the actual application requirements, you can configure multiple application services such as PoE power management, port traffic control, VLAN division, and SNMP through the Web network management mode.

## TECHNICAL SPECIFICATION

Model	XC-IS3824GM
Fixed Port	24*10/100/1000Base-T ports (Data) 4*1000Base-X uplink SFP slot ports (Data) 1*Console RS232 port (115200, N,8,1)
Ethernet Port	Port 1-24 support 10/100/1000Base-T, auto-sensing,Full/half duplex MDI/MDI-X self-adaption

Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP ( $\leq$ 100 meter) 100BASE-TX: Cat5 or later UTP ( $\leq$ 100 meter) 1000BASE-T: Cat5e or later UTP ( $\leq$ 100 meter)
Optical Fiber Port	Gigabit SFP optical fiber interface, default matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)
Optical Cable/ Distance	Multi-mode: 850nm / 0 ~ 550M (1.25G), 850nm / 0 ~ 300M (10G); single mode: 1310nm / 0 ~ 40KM, 1550nm 0 ~ 120KM.
Network Management Type	L2+
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T IEEE802.3u 100Base-TX, IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-X IEEE802.3ae 10GBase-LR/SR IEEE802.3x
Forwarding Mode	Store and Forward (Full Wire Speed)
Switching Capacity	56Gbps (non-blocking)
Forwarding Rate@64byte	41.67Mpps
MAC	32K
Buffer Memory	32M
Jumbo Frame	9.6K
LED Indicator	Power: PWR (yellow), system:SYS (yellow); network:Link (yellow); Fiber port : L/A (green)
Reset Switch	Yes, support one key to restore factory settings
Power Consumption	Standby<10W; Full Load<30W
Heat Dissipation	Low noise fan active cooling
Power Supply	Built-in power supply, AC 100~240V 50-60Hz
Operation TEMP / Humidity	-40~+80°C;5%~90% RH Non condensing

Storage TEMP / Humidity	-40~+125°C;5%~95% RH Non condensing
Dimension (L*W*H)	440*300*45mm
Net /Gross Weight	<4.4kg / <5.0kg
Installation	Desktop type ,19-inch 1U cabinet installation
Lightning protection / protection level	<p>Lightning protection: 6KV 8/20us; Protection level: IP30</p> <p>IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge</p> <p>IEC61000-4-3(RS):10V/m(80~1000MHz)</p> <p>IEC61000-4-4(EFT): power cable: ±4kV; data cable: ±2kV</p> <p>IEC61000-4-5(Surge): power cable:CM±4kV/DM±2kV; data cable: ±4kV</p> <p>IEC61000-4-6(radio frequency transmission):10V(150kHz~80MHz)</p> <p>IEC61000-4-8(power frequency magnetic field):100A/m;1000A/m ,1s to 3s</p> <p>IEC61000-4-9(pulsed magnet field):1000A/m</p> <p>IEC61000-4-10(damped oscillation):30A/m 1MHz</p> <p>IEC61000-4-12/18(shockwave):CM 2.5kV, DM 1kV</p> <p>IEC61000-4-24(common-mode transmission):30V; 300V,1s</p> <p>FCC Part 15/CISPR22(EN55022): Class A</p> <p>IEC61000-6-2(Common Industrial Standard)</p>
Mechanical Properties	<p>IEC60068-2-6 (anti vibration)</p> <p>IEC60068-2-27 (anti shock)</p> <p>IEC60068-2-32 (free fall)</p>
Certification	CCC; CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS
Warranty	5 years, lifelong maintenance.
Interface	<p>IEEE802.3X (Full-duplex)</p> <p>Port temperature protection setting</p> <p>Port green Ethernet Energy-saving setting</p> <p>Broadcast storm control based on port speed</p> <p>The speed limit of the message flow in the access port.</p> <p>The minimum particle size is 64Kbps.</p>

Layer 2+ Features	L2 network management, IPV4/IPV6 management  L2 soft routing forwarding,  Static route, Default route @ 128 pcs, APR @ 1024 pcs
VLAN	4K VLAN based on port, IEEE802.1q  VLAN based on the protocol  VLAN based on MAC  Voice VLAN, QinQ configuration  Port configuration of Access, Trunk, Hybrid
Port Aggregation	LACP, Static aggregation  Max 14 aggregation groups and 8 ports per group.
Spanning Tree	STP (IEEE802.1d), RSTP (IEEE802.1w), MSTP (IEEE802.1s)
Industrial Ring	G.8032 (ERPS), Recovery time less than 20ms
Network Protocol	250 Ring at most, Max 1024 devices per ring.
Multicast	MLD Snooping v1/v2, Multicast VLAN  IGMP Snooping v1/v2, Max 250 multicast groups, Fast log out
Port Mirroring	Bidirectional data mirroring based on port
QoS	Flow-based Rate Limiting  Flow-based Packet Filtering  8*Output queues of each port  802.1p/DSCP priority mapping  Diff-Serv QoS,Priority Mark/Remark  Queue Scheduling Algorithm (SP, WRR, SP+WRR)
ACL	Port-based Issuing ACL, ACL based on port and VLAN  L2 to L4 packet filtering, matching first 80 bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc.

Security	IP-MAC-VLAN-Port binding ARP inspection,Anti-DoS attack AAA & RADIUS, MAC learning limit Mac black holes,IP source protection IEEE802.1X & MAC address authentication Broadcast storm control,Backup for host datum SSH 2.0, SSL,Port isolation,ARP message speed limit User hierarchical management and password protection
DHCP	DHCP Client,DHCP Snooping, DHCP Server,DHCP Relay
Management	One-key recovery Cable Diagnose,LLDP Web Management (HTTPS) NTP,System work log,Ping Test CPU instant utilization status view Console/AUX Modem/Telnet/SSH2.0 CLI Download & Management on FTP, TFTP, Xmodem, SFTP, SNMP V1/V2C/V3 NMS - smart network management system platform (LLDP+SNMP)
System	Category 5 Ethernet network cable Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Microsoft Internet Explorer10 or later; TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in a network

## PACKING LIST

CONTENT	QTY	UNIT
24 Ports L2+ Managed Industrial Ethernet Switch (XC-IS3824GM)	1	SET
User Guide	1	PC
Warranty Card	1	PC