



OPERATING TEMPERATURE

tc. 75°C ta. 60°C

Features :

- » Diffused Cool White Light
- » Slim Led Light For Electrical Panel Industry
- » Powder Coated Aluminum Main Body
- » Suitable for Ceiling and Wall Mounting
- » Sleek & Compact Design
- » Longer Life Of 50000 Hrs.
- » Quick And Easy To Install
- » Integrated Power Unit
- » Mounting : Clamp, Screw and Magnet fixing

RoHS CE

Specifications :

LED Type	: SMD2835, LM80
Color Temp (CCT)	: 6500K
Beam Angle	: 120°
CRI (min)	: 80
Housing Material	: PC + Aluminium
Luminous	: 100/Watt

Product Selection Guide :

<u>MODEL CODE</u>	<u>ON/OFF SWITCH</u>	<u>INPUT SUPPLY</u>	<u>SUPPLY</u>	<u>CAPACITY</u>
XX - LTL	S	230	A	6W
	S – on/off Switch	230 – 230V AC	A – AC	3W
	C – without Switch	110 – 110V AC	D - DC	6W
		24 – 24V DC		8W
				10W
				12W

Example : XX-LT**LS**-**230**-**A**-**6W** --> Description : **6W**, **230V** **AC** 50-60Hz, **On/Off Switch**